

ZANJADORA CON OPERADOR A PIE

C14

DIMENSIONS	U.S.	METRIC
Width	31.5 in	800 mm
CL to Right	17.3 in	439 mm
CL to Left	14 in	356 mm
Headshaft	13 in	330 mm
Length (Up to)	84 in	2.1 m
Height, Transport (Up to)	48 in	1.2 m

POWER		
Briggs & Stratton	Briggs & Stratton 2100 Series	
Fuel	Gasoline	
Cooling	Air	
Number of Cylinders	1	
Manufactures Net HP rating	13.5 hp	10 kW
Rated Speed	3600 rpm	
Fuel Consumption @ Rated Power	1.3 gph	4.9 lph
Starting	Rope pull	

POWER TRAIN		
Ground drive	Hydraulic, Infinite variable from zero to maximum, speed and direction control	
Digging Chain Drive	Hydraulic direct drive, one speed forward, reverse	
Pump Drive	Direct to engine	
Track Width	16 x 6.5-8	
Hydraulic	Direct Drive	
Digging Chain	19K/33K/35K	
Ground Pressure	TBD	

OPERATION

Travel Speed (Fwd)	TBD
Travel Speed (Rev)	TBD
Diggin Chain Speed (Std)	SUM
19K	416
33/35K	351 ft/min
Spoils Handling	Auger, single, open end
Auger Diameter	17 in
Trencher Cleaner Type	Mechainical
Trench Cleaner Size	4-6 in
Operating weight (up to)	TBD

HYDRAULIC SYSTEM

Digging drive pump capacity	6 gpm
Ground Drive	
Dual Speed	
Transit	7.5 gpm
Digging	1.5 gpm
Filtration	10 micron absolute

FLUID CAPACITES

Fuel	1.7 gal
Hydraulic	7 gal

TRENCH SIZE (MAX)

Depth	24 in
Width	6 in

NOISE LEVEL

Operator	TBD
Overall	TBD

VIBRATION LEVEL

Operator's hand	Less than 2.5m/s ²
-----------------	-------------------------------