

# ZANJADORA CON OPERADOR A PIE C12

<b>DIMENSIONS</b>	<b>U.S.</b>	<b>METRIC</b>
Width	31.5in	800mm
Cl to Right	17.3in	439mm
CL to Left	14in	356mm
Headshaft	13in	330mm
Length (Up to)	84in	0mm
Height, Transport (Up to)	48in	1.2m

<b>POWER</b>		
Briggs & Stratton	Honda GX390	
Fuel	Gasoline	
Cooling	Air	
Number of Cylinders	1	
Manufactures Net HP rating	12 HP	8.7 kW
Rated Speed	3600 RPM	
Fuel Consumption @ Rated Power	0.92 GPH	3.5 LPH
Starting	Rope Pull	

<b>POWER TRAIN</b>	
Ground drive	Hydraulic, Infinite variable from zero to maximum, speed and direction control
Digging Chain Drive	Hydraulic direct drive, one speed forward, reverse
Pump Drive	Direct to Engine
Track Width	16 X 6.5-8
Hydraulic	Direct Drive
Digging Chain	19K/33K/35K
Ground Pressure	TBD

## OPERATION

Travel Speed (Fwd)	TBD
Travel Speed (Rev)	TBD
Diggin Chain Speed (Std)SUM	
19K	416
33/35K	351 ft/min
Spoils Handling	Auger, Single, Open end
Auger Diameter	17in
Trencher Cleaner Type	Mechainical
Trench Cleaner Size	4-6in
Operating weight (up to)	TBD

## HYDRAULIC SYSTEM

Digging drive pump capacity	6
Ground Drive	
Dual Speed	
Transit	7.5 GPM
Digging	1.5 GPM
Filtration	10 Micron Absolute

## FLUID CAPACITES

Fuel	1.6 Gal
Hydraulic	7 Gal

## TRENCH SIZE (MAX)

Depth	24in
Width	6in

## NOISE LEVEL

Operator	TBD
Overall	TBD

## VIBRATION LEVEL

Operators hand	Less than 2.5m/s <sup>2</sup>
----------------	-------------------------------