

C200 FORESTRY MULCHER

For the ultimate in compact, powerful mulchers, look no further than Rayco's C200R. Its narrow profile makes the C200R the ultimate for ROW clearing on narrow lines as well as for use in larger-scale clearing projects. The operator cabin is comfortable and spacious, with a high-backed, heated seat with air-ride suspension. The rear fan is auto-reversing, reducing maintenance time.

FEATURES AND BENEFITS

- Powerful 188-HP Isuzu diesel engine
- Available with Rayco Predator or Denis Cimaf Mulcher heads, with 6-foot cutting width
- 66 gpm hydraulic output to the mulcher
- Operating weight less than 20,000-pounds
- Heavy-duty rubber track undercarriage
- 20-inch wide rubber tracks
- 2-speed ground travel
- Hydraulic rear winch
- Hydraulic cab tilt
- Certified ROPS/FOPS/OPS Cab
- Rear view camera with dedicated monitor
- Roof-top and side escape hatches
- High-output LED work lights







C200 FORESTRY MULCHERSPECIFICATIONS

GENERAL

Max Mowing Height

Cutter Teeth

200RA US (METRIC

200SA US (METRIC

	- JUS (INICIAIC)	03 (IVIETRIC)	
Weight of Carrier with Winch	9	4-	
& FM200-6DR Mulcher	20,760 lb (9,4	20,760 lb (9,416.6 kg)	
Length of Carrier with Winch			
& FM200-6DR Mulcher	229.4"(582	229.4"(582.7 cm)	
Height	104.4"(265	104.4"(265.2cm)	
Width	90.8 " (230.6cm)	89.3" (226.8cm)	
Engine	188-HP (140.2 kW)	188-HP (140.2 kW) Isuzu 5.2 L T4F	
Fuel Type	Diesel		
Fuel Capacity	64 gallon (242 L)		
Hydraulic Tank	20 gallon (75.7 L)		
High Flow Hydrostatic	66.1 gpm • 5,800 psi (250 L/min • 400 bar)		
Ground Pressure with FM200-6DR Mulc	her 5.71 psi(39.	.4 kPa)	
Track Width	19.7" (500 mm)	18"(457.2mm)	
Travel Speed High	4.8 mph (7.7 km/h)		
Travel Speed Low	2.7 mph (4.3 km/h)		
Cab Certifications	ROPS ISO 8082 • FOPS ISO 8083 •	OPS ISO 8084/WCB G603	

PREDATOR MULCHER HEAD & DENIS CIMAF MULCHER HEAD

Standard Predator Mulcher Head Model FM200-6DR Weight 3,200 lb (1,451.5 kg) Overall Width 86.25 " (219 cm) Rotor Diameter 16.95 " (43.05 cm) Rotor Speed 2,052 RPM Cutting Width 68.1 " (173 cm)

Optional Denis Cimaf Model	FM200-6CA	
Weight	3,054 lb(1,386 kg)	
Overall Width	87 " (219 cm)	
Rotor Diameter	18" (46 cm)	
Rotor Speed	2,500 RPM	
Ground Pressure	5.31 psi(36.6 kPa)	
Cutting Width	74 " (189 cm)	
Max Mowing Height	102.8" (261.1 cm)	

Cutter Teeth 27 Planer Knives



Protected LED Lights (9700 total lumens)



Rooftop escape hatch and full color, dedicated backup camera display



102.8" (261.1 cm)

36 Carbide Tipped

20,000 lb capacity, hydraulic winch



20" (500mm) wide rubber track

