

MADE FOR MORE TO KEEP PACE WITH YOU

FORESTRY MULCHER & HYDRA-STUMPER

FEATURES AND BENEFITS

- 415-hp CAT Diesel engine
- Rayco-exclusive elevated cooling system
- Reversing fan for upper coolers
- Heavy-duty undercarriage
- Remote track tension system w/tension monitor
- 2-speed ground travel
- Hydraulic rear winch
- Hydraulic cab tilt
- Certified ROPS/FOPS/OPS cab
- Rear view camera
- Heated seat w/air-ride suspension
- Roof-top escape hatch
- High-output led work lights
- Color LCD display to monitor engine and hydraulic functions
- Dual-drive predator mulcher head w/variable displacement motors
- Hydra-Stumper stump cutter head with 48-inch diameter Monster Tooth™ wheel
- Predator Mulcher Head and Hydra-Stumper interchangeability



Rayco's exclusive elevated cooling design places engine radiators in both the rear of the engine compartment and in the limb riser for maximum cooling in even the harshest environments.



Hydraulic rear winch with 35,000-pound capacity.





T415 FORESTRY MULCHER & HYDRA-STUMPER SPECIFICATIONS



PREDATOR MULCHER HEAD

| Mulcher Head Model | FM415-8R | FM415-8R | |
|---------------------------|--|----------|--|
| Weight | 7,200 lb | 3,266 kg | |
| Overall Width | 112 " | 284.5 cm | |
| Rotor Diameter | 27 " | 68.5 cm | |
| Ground Pressure | 5.74 psi | 39.6 kPa | |
| Cutting Width | 91.25 " | 232 cm | |
| Max Mowing Height | 74 " | 188 cm | |
| Cutter Teeth | 45 Rayco Single Bolt Teeth + 4 Rayco Single Bolt Extra Carbide Teeth | | |

HYDRA-STUMPER CUTTER HEAD

| Hydra-Stumper Model | CB415 | | CB415 |
|---|----------|---------------------|----------|
| Weight | 6,500 lb | | 2,950 kg |
| Wheel Diameter | 48 " | | 122 cm |
| Wheel Thickness | 3" | | 7.6cm |
| Cutter Wheel RPM | 705 RPM | | 705 RPM |
| Drive Belt | | Gates Polychain® GT | |
| Ground Pressure with Winch and Stumper Head | 5.68 psi | | 39.2 kPa |
| Cutter Teeth | | 56 Monster Tooth™ | |
| Below Ground Cutting Level | 46 " | | 116.8 cm |
| Above Ground Cutting Level | 8'-10" | | 2.7 m |
| Cutting Width | 9' | | 2.74 m |

