

T1360

PERFORMANCE SPECIFICATIONS

ENGINE	
Engine	CAT C13 Acert turbocharged diesel, Tier 3
Rating	440 HP (328 kW)
Fuel Capacity	Duel Tanks: 250 U.S. Gallons (946 L)
Hydraulic System	Single bolt-on Tank: 200 U.S. Gallons (757 L)
Fuel Consumption	22.8 U.S. Gallons (86.3 L) / hour at full HP

TRACK DRIVE	
Speed	2 MPH (3.2 KPH)
Track Control	Independent proportional electric over hydraulic
Load Control	Microcontroller with bypass
Crawlers	CAT D-7 components
Grouser	24 in. (610 mm) wide, low-profile double grousers

Fully enclosed, air conditioned, heated and pressurized cab	
Elevation	36 in. (915 mm)

OPERATOR STATION	
------------------	--

DIGGING ASSEMBLY	
Heavy duty mechanical chain drive. Power shift transmission with (3) trenching speeds & reverse	
Tailwheel	48 in. (1219 mm) diameter forged (not plate welded) ring

CONVEYOR	
----------	--

Belt Width	30 in. (762 mm)
Belt Speed	0 to 800 FPM (244 MPM)

STANDARD	OPTIONAL
Bottom tail wheel transition wear plates	Automatic laser control for grade
Noise abatement equipment	Automatic laser control for steering
Personnel guard	Auxiliary truck loading conveyor
Work lights (2 fore / 2 aft)	Berm scrapers
	Crumb shoe
	Cold weather package

DIMENSIONS	
Length	29 ft. 1 in. (8.9 m)
Width	9 ft. 9 in. (3 m)
Height	11 ft. (3.4 m)
Transport Length	38 ft. (11.6 m) with 8 ft. (2.4 m) boom

WEIGHTS	
Total Weight	138,000 - 148,000 lbs. (62,596 - 67,131 kg)